PMI® HUDSON CLASSIC **PROFESSIONAL**



PMI's classic EZ-Bend 16 carrier construction combined with the toughest nylon on the market makes PMI ropes some of the toughest in the world. PMI ropes will always beat 32, 40, and 48 carrier designs made with lesser quality nylons hands down in abrasion and real-world durability tests. Although all diameters of PMI Classic rope are 16 carrier sheath design, the denier (thickness) of each diameter's sheath is different. It is carefully designed to provide the maximum abrasion resistance, "grab" the core to minimize sheath slippage, and provide the desired hand for the intended applications.

Key Features:

NFPA Certified . 16 carrier construction . CI 1801 . Third party certified by UL (Underwriters Laboratories) . CE . Torsionally balanced, continuous filament 6,6 nylon. Available in many colors. Also available in custom colors & lengths

9 mm (23/64")

Weight: 53 g/m » MBS: 18.3 kN (4114 lbf)

Elongation: 3.7% at 300 lbf | 5.4% at 600 lbf | 7.6% at 1000 lbf

Elongation at 10% MBS: 4.3%

Standard Colors Available: WB, OB, BK

🛨 USA MADE 🛨 CERTIFIED EN 1891-A CI1801, Static **BERRY COMPLIANT**

10 mm (25/64")

Weight: 66 g/m » MBS: 30.1 kN (6769 lbf)

Elongation: 1.9% at 300 lbf | 4.0% at 600 lbf | 6.4% at 1000 lbf

Elongation at 10% MBS: 4.4%-4.6%

Standard Colors Available: WO, OW, RW, BW, BK, OD

🛨 USA MADE 🛨 🖁 **GERTIFIED** NFPA 1983 (2017), T EN 1891-A CI1801, Static

BERRY COMPLIANT

11 mm (7/16")

Weight: 80 g/m » MBS: 32.7 kN (7344 lbf)

Elongation: 1.6% at 300 lbf | 3.0% at 600 lbf | 5.8% at 1000 lbf

Elongation at 10% MBS: 3.4%-4.4%

Standard Colors Available: WB, YB, OB, RB, BB, BK, BL, RD

🛨 USA MADE 🛨

GERTIFIED NFPA 1983 (2017), T ANSI Z359.15 EN 1891-A CI1801, Static **BERRY COMPLIANT**

12.5 mm (1/2")

Weight: 104 g/m » MBS: 43.6 kN (9804 lbf)

Elongation: 0.8% at 300 lbf | 2.0% at 600 lbf | 3.9% at 1000 lbf

Elongation at 10% MBS: 3.6%-4.2%

Standard Colors Available: WO, YW, OW, RW, BW, BK, BL, RD, OD

🛨 USA MADE 🛨 🕽 **CERTIFIED** NFPA 1983 (2017), G ANSI Z359.15 EN 1891-A CI1801, Static

BERRY COMPLIANT

16 mm (5/8")

Weight: 145.0 g/m » MBS: 72.6 kN (16330 lbf)

Elongation: 0.9% at 300 lbf | 1.8% at 600 lbf | 2.4% at 1000 lbf

Elongation at 10% MBS: 3.6%-4.8% Standard Colors Available: YW, BW

★ USA MADE ★ 🖁

CERTIFIED NFPA 1983 (2017), G ANSI Z359.15 CI1801, Static

BERRY COMPLIANT

WHITE/BLACK (WB) ORANGE/WHITE (OW) RED/BLACK (RB) ORANGE/BLACK (OB) RED/WHITE (RW) BLUE/BLACK (BB) RED (RD) WHITE/ORANGE (WO) BLUE/WHITE (BW BLUE (BL) OD GREEN (OD) YELLOW/WHITE (YW) YELLOW/BLACK (YB) BLACK (BK) JUNGLE CAMO (JC)

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: custserv@pmirope.com





Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: custserv@pmirope.com

