



02-008 SPECIFICATION SHEET

ATTRIBUTES:

LINER

13g Salt and Pepper HDPE
A2 Basetek Liner

COATING

Gray Polyurethane
Palm Coating

FEATURES:

- Positive Grip in Dry and Light Oil Environments

APPLICATIONS:

- Appliance Manufacturing
- Automotive Manufacturing
- Construction
- Sheet Metal Handling
- Small Parts Assembly

Armor Guys reference number : 02-008

CATEGORY:

Basetek

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



⚠ This product can expose you to N,N-Dimethylformamide which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

SPECIFICATIONS

LINER MATERIALS	13g Salt and Pepper HDPE A2 Basetek Liner
COATING MATERIALS	Gray Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	XS-XXL

PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ
CASE WEIGHT	17.08/lbs	17.85/lbs	18.84/lbs	20.06/lbs	20.83/lbs	22.48/lbs
CUFF COLOR	■ Purple	■ Red	■ Yellow	■ Brown	■ Black	■ Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4242B	EN Level 2 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F