



ATTRIBUTES:

LINER

13g Green HDPE A4 Basetek Liner

COATING

Black Polyurethane Palm Coating
Also Available in HCT® MicroFoam Nitrile

FEATURES:

- Positive Grip in Dry and Light Oil Environments

APPLICATIONS:

- Automotive Manufacturing
- Metal Stamping
- Steel Handling
- Construction
- Recycling

Armor Guys reference number : 02-014

CATEGORY:

Basetek

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



⚠ This product can expose you to N,N-Dimethylformamide which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

SPECIFICATIONS

LINER MATERIALS	13g Green HDPE A4 Basetek Liner
COATING MATERIALS	Black Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	XS-XXXL

PACKAGING

CASE SIZE	XS	S	M	L	XL	XXL	XXXL
PER CARTON	12DZ						
CASE WEIGHT	23.80/lbs	24.14/lbs	26.23/lbs	27.88/lbs	30.75/lbs	33.06/lbs	36.06/lbs
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue	Gray
ORIGIN	PRC						

PERFORMANCE LEVEL

EN388: 4444D	EN Level 4 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F