

Data sheet
SIRIUS



GENERAL

Art. no.:	A-050	E-class number:	40-02-01-06
EAN:	4030281286943	Customs no.:	84798997
Standard:	MEETS ANSI/ASSP Z359.4 MEETS EN 12841-C MEETS EN 341-2A MEETS OSHA		

Data sheet

SIRIUS

SIRIUS packs the advantages of the best descenders for industrial and rescue applications into an extremely compact design - for better handling and long service life.

SIRIUS lies perfectly in your hand. The auto-returning operating lever has a particularly small radius of motion so that you can work fast, accurately, more comfortably and safely.

During rope insertion, which is intuitive and simple, the carabiner on the harness can stay connected to the device. We designed the route of the rope in such a way that it is protected from twisting and kinking, and from excessive wear and tear.

SIRIUS was developed for extended use under the toughest of conditions. That's why it is made of up to 100 % metal - without any vulnerable synthetic spots.

SIRIUS. Best ergonomics and long service life in its most compact form:

- Outstanding handling thanks to compact design and intuitive route of the rope
- Long-lasting and sturdy: 100% metal
- Auto-locking function, improved an

GENERAL

Internet only:

Explanatory Video for Sirius Descender

SIRIUS descender in practical use

FEATURES











Abseiling speed:	2,00 m/s
Max. service life:	30 Years
Max. number of persons:	2
Rated load:	250 KG
Temperature:	from 60 °C to -30 °C

DIMENSIONS

Size:	47x79x175mm
Weight:	0,51 kg

MATERIAL

Material:	Aluminium, Steel
-----------	------------------

	SIRIUS		
	MEETS ANSI/ASSP Z359.4 MEETS EN 12841-C MEETS EN 341-2A MEETS OSHA	552 lbs (250 kg) 440 lbs (200 kg) 310 lbs (141 kg)	2 2 1
	1.64 - 6.6 ft/s (0.5 - 2 m/s)		
	625 ft (190 m)		
	10-12 mm		
	AL, ST		
	47 x 79 x 175 mm		
	1.12 lbs (.51 kg)		
	A-050		