



HAND PROTECTION

Cut Resistant Low Temperature Gloves

DESCRIPTION

These insulated gloves are constructed with a 10-gauge Tuffalene® UHMWPE shell with a brushed acrylic terry cloth interior for excellent warmth and comfort. The shell is enhanced with a double-dipped palm with three-quarter solid rubber latex and foam rubber latex which provides excellent grip, abrasion resistance, puncture resistance, and water resistance.



INDUSTRY	
Automotive	Farming
Carpentry	Landscaping
Cold Storage	Material Handling
Construction	Warehousing

FEATURES

- One-piece enhanced Tuffalene® UHMWPE seam-free shell with brushed acrylic terry cloth liner for warmth and comfort
- Double-dipped natural rubber latex palm for high gripping qualities, abrasion resistance, puncture resistance and water resistance
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use

ITEM CR330INT

SIZES 8(M)-10(XL)

- ANSI/ISEA 105 Cut Level A4
- ASTM F2992-15 Results = 1,598 grams
- ANSI/ISEA 105 Abrasion Level 3
- ANSI/ISEA 105 Puncture Level 3
- ANSI/ISEA 105 Puncture Results: 91 Newtons
- EN 388 Levels: 2X42D



SPECIFICATIONS

SHELL	SHELL COLOR	GAUGE	LINER	COATING	COATING COLOR	COATING TYPE	CUFF	FINISH
Tuffalene® UHMWPE	White and Blue	10-Gauge	Acrylic Terry Cloth	Rubber Latex	Black	Palm over 3/4	Knit Wrist	Foam over Smooth
ANSI CUT	ASTM F2992-15 RESULTS	ANSI ABRASION	ANSI PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS			
Level A4	1,598 Grams	Level 3	Level 3	91 Newtons	2X42D			

PACKAGING

	QUANTITY	8(M)	9(L)	10(XL)
PAIR UPC	1	NA	NA	NA
INNER PACK UPC	12/PACK	0816368029108	816368029115	816368029122
CASE GTIN	6 PK/CASE	10816368029105	10816368029112	10816368029129
CASE WEIGHT (IN POUNDS)		23.5	26.1	30.3
OVERCAST COLOR		Green	Brown	Black

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com

