Drill-Drive Kits Add More Power to our Powerful Worm Gear Hand Winches

A variety of our hand winches can be operated with a power drill – making your job faster and easier. Quickly release the winch handle and lift up to 2,500 lbs. with the assistance of a DeWalt power drill and 1-1/8" socket adapter. Our packaged kits include power drill options that meet or exceed our engineering standards for proper winch operation. These kits are ideal for those lifts where more speed and less fatigue are desired.

* 100% ball-bearing construction provides durability and longer tool life.

* Mechanical clutch in low gear to provide control of reactionary torque. * Bail handle and 2-position side handle provide maximum leverage and control.

* Mechanically controlled 2-speed range (use lowest speed setting to prevent overload/failure).

* Triple gear reduction provides increased torque and reduces gear stress.

* Metal gear housing for durability and reliability.



Thern products are not for lifting people or things over people.
5712 Industrial Park Road • Winona, MN 55987 • TF: 1-800-843-7648 • P: 1-507-454-2996 www.thern.com



4WM2

2W40



PERFORMANCE

Heavy-Duty Right Angle Drill Kit Model ED330-DW11

120 volt, 60 Hz, single phase AC power

SPECIFICATIONS	
Chuck Size	
No Load Speed	330rpm
Amps	11Amps
Shipping Weight	



Heavy-Duty Cordless Drill Kit 20V/60V Lithium Ion Battery and Fast Charger

Model ED300-DW06

SPECIFICATIONS

1/2"
300rpm
amp/hr
24 lbs

ED30-DW11 ED300-DW06	Winch Model	Wire Rope Diameter	Load (Ibs)	Distance (ft)	Lift Time (minutes)
	4WM2	1/4"	500	135*	15
			1000	75	10
			1500	45	7
	2W40	5/16"	500	200	15
			1000	100	9
			1800	50	5
	2W40 5/16"				





Super-Duty Cordless Drill Kit 20V/60V Lithium Ion Battery and Fast Charger

Model ED400-DW09

SPECIFICATIONS

Chuck Size	
No Load Speed (low range)	400rpm
Battery	9.0 amp/hr
Shipping Weight	

60	Winch Model	Wire Rope Diameter	Load (lbs)	Distance (ft)	Lift Time (minutes)
ED400-DW09	4WM2	1/4"	800	200*	15
			1200	90	9
			1500	45	5
	2W40 5/16"	1000	200	12	
		5/16"	2000	100	7
			2500	50	4

