

7016BFD

Contractor+ Front 1D Standard Non-belted Full Body Harness

Features :

- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple adjustment.
- Breathable padded air-mesh shoulder yoke delivers added user comfort
- Paired lanyard parking keepers provide balanced function for single and twin-leg personal SRLs
- Plated alloy steel dorsal and sternal D-rings with mating buckle chest and tongue buckle leg closures
- Uncommonly outfitted with 9 grommeted leg adjustment positions for a wider range of fit
- Complies with ANSI Z359.11-2014



Material Specifications		Performance Specifications		Compliant With:	
Webbing	Polyester; 5,000 lb min. static strength	Static Strength	3,600 lb min.	ANSI	Z359.11-2014
D-rings	Plated alloy steel; 5,000 lb min. static strength	ANSI User Capacity	130 to 310 lb max.	OSHA	1926.502 and 1910.66
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength	OSHA User Capacity	130 to 425 lb max.		

Sizes & Part Numbers						
7016BFDXS - XS	7016BFDS - Small	7016BFDM - Medium	7016BFDL - Large	7016BFDXL - XL	7016BFD2X - 2X	7016BFD3X - 3X