

# 3M<sup>™</sup> PELTOR<sup>™</sup> Electronic Earplug, EEP-100 **Technical Data Specifications**

| Model           |  |
|-----------------|--|
| Microphone Type |  |

Omni-directional

| Earpiece Power / Electrical Characteristics |                           |  |  |  |  |  |
|---|---------------------------|--|--|--|--|--|
| Earpiece Battery Type                       | Lithium Ion               |  |  |  |  |  |
| Earpiece Battery Life                       | Up to 16 Hours            |  |  |  |  |  |
| Earpiece Battery Charge Time                | Approximately 180 Minutes |  |  |  |  |  |
| Earpiece Volume Steps                       | Low, Normal, High         |  |  |  |  |  |
| Case USB Type                               | Micro B                   |  |  |  |  |  |

| Standards         |  |
|-------------------|--|
| Waterproof Rating | Complies with IP54 with cover and USB port closed. |
| NRR               | Tested in accordance with<br>ANSI S3.19-1974       |

| Physical Characteristics  |   |
|---|---|
| Case Size (L x W x H)   | 89.6 mm x 61.6 mm x 27.3 mm                           |
| Case Material   | ABS   |
| Earpiece Keypad   | One button operation<br>(On / Off / Volume Selection) |
| RoHS Compliance   | RoHS II   |
| Weight: Box containing charger,<br>2 Earplugs,4 pair communications<br>Eartips, USB cable | 8.46 oz   |
| Weight: Charger   | 2.01 oz   |
| Weight: 1 earpiece  | 0.13m oz  |
|   |   |

# **Environmental Characteristics** Storage temp (complete kit)

| 3 Month<br>1 Month      | -4°F to 68°F<br>-4°F to 113°F<br>-4°F to 140°F |
|-------------------------|--|
| Earpiece Operating temp | -4°F to 122°F                                  |
| Charger Operating temp  | 32°F to 113°F                                  |
|                         |  |

EEP-100 with 3M<sup>™</sup> Ultrafit<sup>™</sup> Eartips

|                         | -    | -    | -    |      |      |      |      |      |      |       |           |
|-------------------------|------|------|------|------|------|------|------|------|------|-------|-----------|
| Frequency (Hz)          | 125  | 250  | 500  | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 | NRR   | CSA Class |
| Mean Attenuation (dB)   | 36.2 | 33.7 | 34.7 | 32.0 | 34.5 | 37.4 | 35.6 | 38.0 | 37.5 |       |           |
| Standard deviation (dB) | 5.1  | 5.2  | 5.5  | 3.9  | 3.4  | 5.3  | 6.5  | 4.4  | 5.4  | 23 dB | AL        |

#### EEP-100 with 3M<sup>™</sup> Triple-C Communication Eartips

| Frequency (Hz)          | 125  | 250  | 500  | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 | NRR   | CSA Class |
|-------------------------|------|------|------|------|------|------|------|------|------|-------|-----------|
| Mean Attenuation (dB)   | 34.5 | 30.6 | 36.3 | 35.2 | 35.5 | 38.6 | 37.6 | 44.6 | 45.7 | 27 dB |           |
| Standard deviation (dB) | 4.2  | 3.9  | 4.1  | 3.0  | 3.5  | 3.3  | 3.8  | 3.6  | 4.3  | 27 08 | AL        |

#### EEP-100 with 3M<sup>™</sup> Skull Screws<sup>™</sup> Eartips (not included)

| Frequency (Hz)          | 125  | 250  | 500  | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 | NRR   | CSA Class |
|-------------------------|------|------|------|------|------|------|------|------|------|-------|-----------|
| Mean Attenuation (dB)   | 36.3 | 35.7 | 39.8 | 41.4 | 40.4 | 43.0 | 41.9 | 48.2 | 46.0 | 30 dB |           |
| Standard deviation (dB) | 5.3  | 5.5  | 5.5  | 4.2  | 3.4  | 4.6  | 3.5  | 4.6  | 4.2  | 30 dB | AL        |

### Hearing Protection Products\*

This hearing protector helps reduce exposure to hazardous noise and other loud sounds Misuse or failure to wear hearing protection at all times when exposed to hazardous noise may result in hearing loss or injury. For correct use, consult supervisor and User Instructions, or call 3M Technical Service. If your hearing seems dulled or you hear a ringing or buzzing during or after any noise exposure (including gunfire), or for any other reason you suspect a hearing problem, leave the noisy environment immediately and consult a medical professional and/or your supervisor.

3M strongly recommends individual fit testing of hearing protectors. If the NRR is used to estimate typical workplace protection, 3M recommends that the noise reduction value be reduced by 50% or in accordance with applicable regulations.

NOTE! When worn according to the User Instructions, this hearing protector helps reduce exposure to both continuous noises, such as industrial noises and noises from vehicles and aircraft, as well as very loud impulse noises, such as gunfire. It is difficult to predict the required and/or actual hearing protection obtained during exposure to impulse noises. For gunfire, the weapon type, number of rounds fired, proper selection, fit and use of hearing protection, proper care of hearing protection, and other variables will impact performance. If your hearing seems dulled or you hear a ringing or buzzing during or after any noise exposure (including gunfire), or for any other reason you suspect a hearing problem, your hearing may be at risk. To learn more about hearing protection for impulse noise, please visit www.3M.com/hearing.

# **3M Personal Safety Division**

3M Center, Building 235-2NW-70 St. Paul, MN 55144-1000 3M.com/PELTOR For More Information Technical Service 1-800-665-2942

Customer Service 1-800-328-1667

3M Personal Safety Division products are for occupational use only. 3M, UltraFit and Skull Screws are trademarks of 3M Company, used under license in Canada.

© 3M 2018. All rights reserved. Please recycle. Printed in U.S.A.

The warranty does not cover any damage caused by neglected maintenance or careless handling.

For more information on maintenance, please see the user instruction For complete warranty condition, contact your dealer or local 3M office

3M does not accept liability of any kind, be it direct or consequential (including, but not limited by having or any kind, bert uner or consequential including, but not limited by loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict

3M's liability for death or personal injury arising from its negligence.

**3M Hearing Solutions** 

# **Hearing Protection and Situational Awareness**

# 3M<sup>™</sup> PELTOR<sup>™</sup> Electronic Earplug, EEP-100

3M<sup>™</sup> PELTOR<sup>™</sup> Electronic Earplug, EEP-100, can help users protect their hearing, but also helps improve situational awareness and face-to face communication.

# **Compact Hearing Protection with Improved Situational Awareness**

# Communication

The earpieces are rechargeable via a USB jack on the charging case. The case also provides easy and convenient storage of the earpieces when not being used.

The small and lightweight design helps improve the overall comfort and user experience, and makes it compatible with most head-borne 3M personal protective equipment (PPE), such as helmets and face shields.

## Butto Intuitive one-button operation turns unit on, off, and selects from 3 volume settings.

**Microphone Port** Helps minimize wind noise. Additional windscreen accessory also available.

Sealing Ring Rubber sealing ring helps protect earplugs in wet and dirty environments.

Charging Case Pocket-sized storage and charging container. Including charging status indicator.

3M<sup>™</sup> PELTOR<sup>™</sup> Electronic Earplugs help protect against harmful noise, while allowing ambient sounds to be heard at a level below 82dB. It increases your ability to communicate with nearby colleagues, as well as hearing warning signals, approaching vehicles, or sounds in machines and processes.

# 3M<sup>™</sup> PELTOR<sup>™</sup> Electronic Earplug, EEP-100 Ordering Information

| Number | 3M ID Number | SAP ID Number | Product Description                         |
|--------|--------------|---------------|---|
|        | 70071730793  |               | 3M™ PELTOR™ Electronic Earplug Kit, EEP-100 |

# Accessories and Earplug Tips

Product N

EEP-100

| Product Number | 3M ID Number | SAP ID Number | Product Description   |
|----------------|--------------|---------------|---|
| TEP-CORD       | 70071673795  | 7100074090    | Replacement Cord  |
| 370-TEPL-25    | 70071673746  | 7100066388    | UltraFit™ Communication Tips Replacement,<br>Large, 25 pairs  |
| 370-TEPM-25    | 70071673738  | 7100066387    | UltraFit™ Communication Tips Replacement,<br>Medium, 25 pairs |
| 370-TEPS-25    | 70071673720  | 7100066371    | UltraFit™ Communication Tips Replacement,<br>Small, 25 pairs  |
| CCC-GRM-25     | 70071675212  | 7100103087    | Triple-C Communication Ear tips, 25 pairs                     |
| 370-1019-10    | 70071615275  |               | Skull Screw™, Communication Tips, 10 pairs                    |
| TEP-WINDSCREEN | 70071675907  | 7100113748    | Foam Windscreen for TEP/LEP and EEP                           |

### **Hearing Protection**

Replaceable communications eartip helps provide hearing protection in noisy environments. Multiple sizes and types designed to fit most ear canals



## Rechargeable

Charging contacts recharge the unit while in the case. Li-ion battery provides up to 16 hours of continuous operation.

## Design

Corner radius designed to help soften contact zone and increase comfort

> Clear lid Enables easy visability of charging status when closed.

# Micro B USB Charging Port

USB port enables the charging of the earplugs when plugged into a computer or wall socket (USB cable included).