TERRADAPTOR™ TRIPOD SYSTEM





TerrAdaptor[™] Specifications

Weight: 90 lbs (40.823 kg)

Standards applicable: NFPA 1983 (2012) G, CE, EN 795

Color: Orange and gray

The TerrAdaptor[™] isn't just for straight lifts over holes. Its variability enables you to use it over an edge, in an elevator shaft, over a trench, or atop a grain bin.

- Symmetric tripod and quadpods are the only systems of their kind to be certified by UL to NFPA 1983 (2006 ed.)
- The TerrAdaptor can be used in countless nonstandard configurations
- Reaches a height of 10 ft., but additional leg extensions (approximately 4 ft.) can be bought
- To transitions your tripod to a quadpod, you can purchase the Quadpod Attachment Kit seperately

SM230100N \$4,400.00

COMPLIANT

NFPA 1983 (2012), G CE EN 795







A-Frame/Bipod Great high directional for offsets and highlines

Horizontal Span

trench rescue

Best for collapse or

Gin Pole/Monopod Perfect option for a lightweight high directional



Easel Leg Tripod Easel leg provides extra support to A-Frame

MULTI POD

HARDWARE TERRADAPTOR[™]



Symmetric Tripod

HEIGHT	MBS	APPLICABLE STANDARDS
4'	12,200 lbf	NFPA, CE, ASTM
7′	12,100 lbf	NFPA, CE, ASTM
13′	4,600 lbf	

Horizontal Span

SPAN	LEG TUBES	MBS	APPLICABLE STANDARDS
4′	SINGLE	5,600 lbf	N/A
4′	DOUBLE	8,200 lbf	N/A
6′	SINGLE	3,500 lbf	N/A
6′	DOUBLE	5,900 lbf	N/A
8′	DOUBLE	4,000 lbf	N/A

Gin Pole/Monopod

HEIGHT	MBS	APPLICABLE STANDARDS
8′	4,500 lbf	N/A

Symmetric Quadpod

HEIGHT	MBS	APPLICABLE STANDARDS
4′	13,000 lbf	NFPA, CE, ASTM
7′	12,200 lbf	NFPA, CE, ASTM
13′	V,100 lbf	ASTM

Quadpod Attachment System:

- •Head attachment
- •Leg kit with rocker foot
- •Hobble plate and basket
- •Center leg clamp with 3 load locking pins each
- •Main attachment pin
- Rope hobble section
- SM230105 \$1,295.00

A-Frame/Bipod

HEIGHT	MBS	APPLICABLE STANDARDS
7′	5,600 lbf	ASTM



Quadpod provides greater strength and a smaller footprint



Articulating Foot • Swivels on a stainless steel ball

For extreme wide angels it can rotate to a flat position
Rubber pad allows it to be used on concrete

WEIGHT: 1.02 lbs (460 g) SM230530 \$115.00





Talon Foot • Two spikes allow it to perch on edges of walls and catwalks • Lashes securely to pipes, beams and rails

WEIGHT: 5.7 oz (161 g) SM230510 \$38.00



QuickLash

Install an auxiliary anchor point at any timeIdeal for attaching gear to

assist with tie backs, redirects and tie-downs • 30 kN strength when loaded

straight along major axis

WEIGHT: 4.2 oz (118 g) SM230370 \$48.00



Sheave Assembly

• Seamless connector maintaining the NFPA strength ratings

- Zinc plated hardened alloy
- steel sealed ball bearings • Supports up to 1/2" diameter cable or rope

TERRADAPTOR[™]

MULTI POD

WEIGHT: 4.0 oz (114 g) SM230360 \$40.00

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: custserv@pmirope.com



